

CLAIMS

I claim:

- Rule 1.126*
1. A resilient seal used in combination with a mobile living quarters having a slide-out room defining an interior space, said mobile living quarters comprising a first sidewall having an exterior side, said first sidewall defining an opening through which said slide-out room is shifted between open and closed positions relative the first sidewall, said slide-out room including a second sidewall spaced from said first sidewall and an end wall defining said interior space, said end wall including a peripheral flange overlapping said first sidewall when said slide-out room is in its said closed position, said seal comprising a mounting portion attached to said first sidewall along said opening and a separate bulb portion, said bulb portion slidably connected to said mounting portion for compressible contact with said flange of said exterior wall when said slide-out room is in its said closed position.
 2. The seal and mobile living quarters of claim 1 including a tongue connector carried by one of said mounting portion and said bulb portion and a groove connector carried by the other of said mounting portion and said bulb portion for releasably facilitating the connection of said bulb portion to said mounting portion.
 3. The seal and mobile living quarters of claim 1 wherein said seal includes a wiper portion extending from said mounting portion toward said second sidewall, said wiper portion maintaining resilient contact with said second sidewall as said slide-out room shifts between said open and closed positions.
 4. The seal and mobile living quarters of claim 3; and a fastener through said mounting portion for attaching said mounting portion to said first sidewall, an adhesive between

said mounting portion and said first sidewall, said fastener covered by said bulb portion.

5. The seal and mobile living quarters of claim 4, and said mounting portion attached to said exterior side of said first sidewall.
6. A resilient seal mountable on a mobile living quarters having a slide-out room defining an interior space, said mobile living quarters including a first sidewall defining an opening through which said slide-out room is shifted between open and closed positions relative the first sidewall, said slide-out room including a second sidewall spaced from said first sidewall and an end wall, said end wall including a peripheral flange overlapping said first sidewall when said slide-out room is in its said closed position, said seal being mountable along said opening between said first sidewall and said second sidewall, wherein said seal comprises a mounting portion attachable to said first sidewall, a separate bulb portion slidably connected to said mounting portion and extending therefrom to enable said bulb portion to contact said flange when said end wall is adjacent said first sidewall.
7. The seal of claim 6, and a wiper portion carried by said mounting portion and extending therefrom to enable it to resiliently contact said second sidewall.
8. The seal of claim 7, and a tongue part carried by one of said mounting portion and bulb portion and a groove carried by the other of said mounting portion and said bulb portion, said tongue part fitting into said groove part to connect said bulb portion to said mounting portion.
9. A method of attaching a seal to a mobile living quarters having a slide-out room, said mobile living quarters including a first sidewall defining an opening through which said slide-out room shifted between open and closed positions relative the first sidewall, said

*Rule 1, cont.
1.126*

slide-out room defined by a second sidewall and an end wall, said end wall including a peripheral flange overlapping said first sidewall when said slide-out room is in its said closed position, said seal including an elongated mounting portion and an elongated bulb seal portion, said method comprising the steps:

- Rule
1.124*
- a) affixing said mounting portion to said first wall adjacent said opening using both adhesive and mechanical fasteners; and,
 - b) attaching said bulb seal portion to said mounting portion so as to locate the bulb portion in compressed engagement with and between said first sidewall and said flange when said slide-out room is in its said closed position.

*10
11*

The method of claim 9 and including the steps of:

- c) sliding said bulb seal portion along said attached mounting to a selected position; and,
- h) maintaining said selected position of said bulb seal portion to said mounting portion by fastening the bulb seal portion to the mounting portion.